



CE Approved, 5 Years Guarantee

Capacity (L)	150	200		300		400		500	
Type of coil pipe	single	single	double	single	double	single	double	single	double
Material of coil pipe(heat exchanger)	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304
Diameter of coil pipe(heat exchanger) (mm)	25	25	25	25	25	25	25	25	25
Thickness of coil pipe(heat exchanger) (mm)	1	1	1	1	1	1	1	1	1
Bearing strength of coil pipe(heat exchanger) bar	10	10	10	10	10	10	10	10	10
Diameter of out tank (mm)	580	580	580	580	580	730	730	730	730
Diameter of inner tank (mm)	480	480	480	480	480	630	630	630	630
Material of inner tank	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304	SUS304
Thickness of inner tank (mm)	1.5	1.5	1.5	1.5	1.5	2.0	2.0	2.0	2.0
Bearing strength of inner tank	8	8	8	8	8	8	8	8	8
Material of out tank	Painted sheet	Painted sheet	Painted sheet	Painted sheet	Painted sheet	Painted sheet	Painted sheet	Painted sheet	Painted sheet
Thickness of out tank (mm)	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
thickness of polyurethane (mm)	50	50	50	50	50	50	50	50	50
Density of polyurethane (kg/ m ³)	38	38	38	38	38	38	38	38	38
Heat exchanging area (m ²)	1	1.5	0.85/0.85	2	1/2	2	1.2/2	2.5	1.5/2.5
Power(kw)	28	30	29/29	51.8	28/52	51.8	29/51.8	62.1	30/62.1
Highness of inner tank (mm)	829	1105	1105	1658	1658	1283	1283	1604	1604
highness of out tank (mm)	959	1235	1235	1788	1788	1413	1413	1734	1734